
Silicon Epitaxial Planar Switching Diode

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Top View
Simplified outline SOD-323 (Bend Lead) and symbol

Features

- AEC-Q101 Qualified
- Fast switching
- Halogen and Antimony Free(HAF), RoHS compliant

Absolute Maximum Ratings (T_a = 25℃)

Parameter		Symbol	Value	Unit
Peak Reverse Voltage		V_{RM}	100	V
Reverse Voltage		V_R	75	V
Average Rectified Forward Current		$I_{F(AV)}$	150	mA
Forward Continuous Current		I_{FM}	300	mA
Surge Forward Current	at t < 1 μs at t < 1 s	I_{FSM}	2 1	A
Power Dissipation [1)]		P_D	200	mW
Operating Junction Temperature Range		T_j	- 55 to + 150	℃
Storage Temperature Range		T_{stg}	- 55 to + 150	℃

Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance from Junction to Ambient [1)]	$R_{\theta JA}$	625	℃/W

[1)] Device mounted on FR-4 substrate PC board, with minimum recommended pad layout.

Characteristics at T_a = 25℃

Parameter	Symbol	Min.	Max.	Unit
Reverse Breakdown Voltage at I_R = 1 μA	$V_{(BR)R}$	75	-	V
Forward Voltage at I_F = 1 mA at I_F = 10 mA at I_F = 50 mA at I_F = 150 mA	V_F	 - - - -	 0.715 0.855 1 1.25	 V
Peak Reverse Current at V_R = 75 V at V_R = 20 V at V_R = 75 V, T_J = 150 °C at V_R = 25 V, T_J = 150 °C	I_R	 - - - -	 1 25 50 30	 μA nA μA μA
Total Capacitance at V_R = 0 V, f = 1 MHz	C_T	-	2	pF
Reverse Recovery Time at I_{rr} = 0.1 X I_R , I_F = 10 mA ,V_R = 6 V, R_L = 100 Ω	t_{rr}	-	4	ns

Electrical Characteristics Curves

Fig. 1 Power Derating Curve




Fig. 2 Capacitance Characteristics




Fig. 3 Reverse Characteristics






Fig. 4 Forward Characteristics




PACKAGE OUTLINE

Plastic surface mounted package; 2 leads **SOD-323(Bend Lead)**



UNIT	A	A_1	b_p	C	D	E	H_E	L_p	Q	P
mm	1.1 0.8	0.1 0	0.4 0.25	0.18 0.09	1.8 1.6	1.35 1.15	2.8 2.3	0.5 0.1	0.5 0.3	0.4 0.3

Recommended Soldering Footprint




Packing information

Package	Tape Width (mm)	Pitch		Reel Size		Per Reel Packing Quantity
		mm	inch	mm	inch	
SOD-323BL	8	4 ± 0.1	0.157 ± 0.004	178	7	3,000

Marking information

" W2 " = Part No.
" III " = Cathode line
Font type: Arial



Disclaimer: Our company reserve the right to make modifications, enhancements, improvements, corrections or other changes to improve product design, functions and reliability, anytime without notice. Semtech Electronics Limited makes no warranties, representations or warranties regarding the suitability of its products for any particular purpose, and does not accept any liability arising from the application or use of any product or circuit such as: Apply to medical, military, aircraft, space or life support equipment and expressly waive any and all liability, including but not limited to special, consequential or collateral damage.