
Silicon Epitaxial Planar Switching Diode

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Top View
Simplified outline SOD-323 and symbol

Features

- AEC-Q101 Qualified
- Fast switching speed
- Ultra-small surface mount package
- For general purpose switching applications
- High conductance
- Halogen and Antimony Free(HAF), RoHS compliant

Absolute Maximum Ratings (T_a = 25℃)

Parameter	Symbol	Value	Unit
Peak Reverse Voltage	V_{RM}	100	V
Reverse Voltage	V_R	80	V
Average Rectified Forward Current	$I_{F(AV)}$	150	mA
Forward Continuous Current	I_{FM}	300	mA
Non-Repetitive Peak Forward Surge Current (at t = 1 μs)	I_{FSM}	0.5	A
Power Dissipation [1)]	P_D	200	mW
Junction Temperature	T_j	150	℃
Storage Temperature Range	T_{stg}	- 55 to + 150	℃

Thermal Characteristics

Parameter	Symbol	Max.	Unit
Thermal Resistance from Junction to Ambient [1)]	$R_{\theta JA}$	625	℃/W

[1)] Device mounted on FR-4 substrate PC board, with minimum recommended pad layout.

Characteristics at T_a = 25℃

Parameter	Symbol	Min.	Max.	Unit
Forward Voltage at I_F = 5 mA at I_F = 10 mA at I_F = 100 mA at I_F = 150 mA	V_F	 0.62 - - -	 0.72 0.855 1 1.25	V
Reverse Leakage Current at V_R = 80 V at V_R = 20 V at V_R = 75 V, T_J = 150 °C at V_R = 25 V, T_J = 150 °C	I_R	 - - - -	 100 25 50 30	 nA nA μA μA
Reverse Breakdown Voltage at I_R = 100 μA	$V_{(BR)R}$	80	-	V
Total Capacitance at V_R = 0.5 V, f = 1 MHz	C_{tot}	-	4	pF
Reverse Recovery Time at I_F = 10 mA, I_{rr} = 0.1 X I_R , V_R = 6 V, R_L = 100 Ω	t_{rr}	-	4	ns

Electrical Characteristics Curves

Fig 1. Power Derating Curve




Fig 2. Capacitance Characteristics




Fig 3. Reverse Characteristics






Fig 4. Forward Characteristics




PACKAGE OUTLINE

Plastic surface mounted package; 2 leads **SOD-323**



UNIT	A	b_p	C	D	E	H_E
mm	1.10 0.80	0.40 0.25	0.15 0.10	1.80 1.60	1.35 1.15	2.80 2.30

Recommended Soldering Footprint



Packing information


Package	Tape Width (mm)	Pitch		Reel Size		Per Reel Packing Quantity
		mm	(inch)	mm	(inch)	
SOD-323	8	4 ± 0.1	0.157 ± 0.004	178	7	3,000

Marking information

" W2 " = Part No.

" III " = Cathode line

Font type: Arial



Disclaimer: Our company reserve the right to make modifications, enhancements, improvements, corrections or other changes to improve product design, functions and reliability, anytime without notice. Semtech Electronics Limited makes no warranties, representations or warranties regarding the suitability of its products for any particular purpose, and does not accept any liability arising from the application or use of any product or circuit such as: Apply to medical, military, aircraft, space or life support equipment and expressly waive any and all liability, including but not limited to special, consequential or collateral damage.