

Silicon Epitaxial Planar Switching Diode

Feature

- AEC-Q101 Qualified
- Low leakage switching double diode
- Very low leakage current
- Medium speed switching times
- Series pair configuration
- Halogen and Antimony Free(HAF), RoHS compliant





1. Anode 2. Andoe 3. Cathode
SOT-23 Plastic Package

Applications

- Low leakage current applications

Absolute Maximum Ratings (T_a = 25℃)

Parameter		Symbol	Value	Unit
Peak Repetitive Reverse Voltage		V_{RRM}	85	V
Continuous Reverse Voltage		V_R	85	V
Continuous Forward Current	Single Diode Double Diode	$I_{F(AV)}$	215 125	mA
Repetitive Peak Forward Current		I_{FRM}	500	mA
Non-Repetitive Peak Forward Surge Current	at t = 1 μs at t = 1 ms at t = 1 s	I_{FSM}	4 1 0.5	A
Power Dissipation [1)]		P_D	250	mW
Operating Junction Temperature Range		T_j	- 55 to + 150	℃
Storage Temperature Range		T_{stg}	- 55 to + 150	℃

Thermal Characteristics

Parameter	Symbol	Max.	Unit
Thermal Resistance, Junction to Ambient [1)]	$R_{\theta JA}$	500	℃/W

[1)] Device mounted on FR-4 substrate PC board, 2oz copper, with minimum recommended pad layout.

Characteristics at T_a = 25℃

Parameter	Symbol	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage at I_R = 100 μA	$V_{(BR)R}$	85	-	-	V
Forward Voltage at I_F = 1 mA at I_F = 10 mA at I_F = 50 mA at I_F = 150 mA	V_F	 - - - -	 - - - -	 0.9 1 1.1 1.25	V
Reverse Current at V_R = 75 V at V_R = 75 V, T_j = 150 °C	I_R	 - -	 - -	 5 80	nA
Total Capacitance at V_R = 0 V, f = 1 MHz	C_{tot}	-	2	-	pF
Reverse Recovery Time at I_F = I_R = 10 mA, I_{rr} = 0.1 X I_R, R_L = 100 Ω	t_{rr}	-	-	3	μs

Electrical Characteristic Curve

Fig 1. Power Derating Curve




Fig 2. Capacitance Characteristics Curve




Fig 3. Reverse Characteristics Curve






Fig 4. Forward Characteristics Curve




Package Outline (Dimensions in mm) SOT-23



Unit	A	A1	B	C	D	E	F	G	L	L1
mm	1.20 0.89	0.100 0.013	1.40 1.20	0.19 0.08	3.04 2.80	2.6 2.2	1.02 0.89	2.04 1.78	0.51 0.37	0.2 MIN

Recommended Soldering Footprint




Packing information

Package	Tape Width (mm)	Pitch		Reel Size		Per Reel Packing Quantity
		mm	inch	mm	inch	
SOT-23	8	4 ± 0.1	0.157 ± 0.004	178	7	3,000

Marking information

" C7 " = Part No.
"YM" = Date Code Marking
"Y" = Year
"M" = Month
Font type: Arial



Disclaimer: Our company reserve the right to make modifications, enhancements, improvements, corrections or other changes to improve product design, functions and reliability, anytime without notice. Semtech Electronics Limited makes no warranties, representations or warranties regarding the suitability of its products for any particular purpose, and does not accept any liability arising from the application or use of any product or circuit such as: Apply to medical, military, aircraft, space or life support equipment and expressly waive any and all liability, including but not limited to special, consequential or collateral damage.